THE POWER TO CREATE BETTER LIGHT ™

Single End Flex Nano Plastic Linear T8

L24T8/8XX/8P-ID

Commercial Grade LED T8 Lamp



Descriptions:

The Flex (Type B) nano plastic lamps are designed to be the perfect retrofit solution to move from traditional fluorescent lamps to energy saving LEDs. This ballast bypass lamp has everything needed built into the lamp with proven energy savings, long life, surge suppression and industry leading safety features. The single ended lamp has power on one end. Nano plastic tube qualfiies any NFS 2 application without breakage.

Features & Benefits:

- Shatterproof Nano Plastic Tube
- NSF2 Rated
- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes non- shunted(rapid start) sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- Suitable for damp and dry locations
- -20° F to 130° F ambient operating temperture
- High performance plastic series
- 5 Year Warranty


Specifications:

Ordering Code	Length (in)	Lamp Wattage	Input Voltage	CCT (K)	Initial Lumens	CRI	Beam Angle	System Efficacy	Life
L24T8/830/8P-ID	24	8	120-277	3000	1100	83	325	138	50000
L24T8/835/8P-ID	24	8	120-277	3500	1100	83	325	138	50000
L24T8/840/8P-ID	24	8	120-277	4000	1100	83	325	138	50000
L24T8/850/8P-ID	24	8	120-277	5000	1100	83	325	138	50000

Copyright © 2008-2024. All Rights Reserved
12257 Florence Ave. | Santa Fe Springs. CA 90670
Toll Free: (866) 933-7736 | Tel.: (562) 529-2938 | Fax: (562) 529-2978
Email: info@espentech.com | www.espentech.com

Wiring Diagram:

Note: Will not operate on shunted sockets. Use only with non-shunted (rapid start) sockets.



DLC Listing:

Ordering Code	DLC Product ID	DLC Product Model	DLC Version
L24T8/830/8P-ID	PL3C9OHOPGI0	L24T8/830/8P-ID	5.0
L24T8/835/8P-ID	PL5SEWQBITO1	L24T8/835/8P-ID	5
L24T8/840/8P-ID	PLNBE5JR2ARS	L24T8/840/8P-ID	5
L24T8/850/8P-ID	PLD9B599654V	L24T8/850/8P-ID	5

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

Copyright © 2008-2024. All Rights Reserved
12257 Florence Ave. | Santa Fe Springs. CA 90670
Toll Free: (866) 933-7736 | Tel.: (562) 529-2938 | Fax: (562) 529-2978
Email: info@espentech.com | www.espentech.com