

# CoreTech Type C Linear T8

# L36T5/840/18G-XT

### **Commercial Grade LED T8 Lamp**



#### **Descriptions:**

The CoreTech (Type C) lamps are designed to be the perfect retrofit solution to move from traditional fluorescent lamps to energy saving LEDs with best controllability. This lamp with paired driver provides full controllability with proven energy savings, long life, surge suppression and industry leading safety features.

#### Features & Benefits:

- Advanced dimming with Pro-DIM technology: 0-10V and/or AB dimming
- No Polarity: lamp ends can be reversed
- Same wiring as fluorescent lamp/ballast system
- UL 1598C for safety
- Full glass as fluorescent T5
- Smooth, Consistent Light
- Suitable for Dry and Damp Locations
- High CRI
- Instant on
- 50,000 hours with no limitation on On/Off Cycles
- Evaluated for use in totally enclosed, recessed luminaires, surface mount wall and ceiling luminaires, outdoor luminaires (open surface mount luminaires with compartment protection from weather)
- For use with Class 2 driver only
- 5 Year Warranty

#### **Specifications:**

Ordering Code	Length (in)	Lamp Current	Lamp Wattage	System Wattage	CCT (K)	Initial Lumens	CRI	Beam Angle	Lamp Efficacy	System Efficacy
L36T5/840/18G-XT	36"	250mA	9	12	4000K	1400	82	240	155	116
L36T5/840/18G-XT	36"	360mA	13	16	4000K	1900	82	240	146	118
L36T5/840/18G-XT	36"	500mA	18	21	4000K	2500	82	240	139	119







# **Wiring Diagram:**













# **DLC Listing:**

Ordering Code	DLC Product ID	DLC Product Model	DLC Version
L36T5/840/18G-XT	N/A	N/A	N/A
L36T5/840/18G-XT	N/A	N/A	N/A
L36T5/840/18G-XT	N/A	N/A	N/A

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

