

Linear T5HE/HO

L48T5HE/8XX/13G-EB-AC

Commercial Grade LED T5 Lamp



Descriptions:

The RetroFlex (Type A) LED lamps provide hassle-free installation with simple lamp-for-lamp replacements for your linear fluorescent T5HE or T5HO retrofit needs. Fully certified to replace original fluorescent lamps, these lamps provide the perfect, hassle-free solution for whatever the project requires. When being used with an instant start, programmed start, or emergency backup ballast, no fixture re-wiring is needed.











Features & Benefits:

- No rewiring needed
- Works with fluorescent electronic T5 ballast
- Long life
- High CRI
- Instant on, no delay
- Convenient and quick installation
- Utilizes existing T5 sockets
- Compatible with controls and sensors
- No Mercury, No UV
- Works in cold temperature applications
- Full Glass Design
- Super Wide View Angle, 240
- 5 Year Warranty

Specifications:


Ordering Code	Length (in)	Lamp Wattage	System Wattage	CCT (K)	Initial Lumens	CRI	Beam Angle	Lamp Efficacy	System Efficacy	Life (hr)
L48T5HE/830/13G-EB-AC	48 in	13W	16W	3000K	1800	83	240	135	115	50000
L48T5HE/835/13G-EB-AC	48 in	13W	16W	3500K	1800	83	240	135	115	50000
L48T5HE/840/13G-EB-AC	48 in	13W	16W	4000K	1800	83	240	135	115	50000
L48T5HE/850/13G-EB-AC	48 in	13W	16W	5000K	1800	83	240	135	115	50000



Copyright © 2008-2024. All Rights Reserved 12257 Florence Ave. | Santa Fe Springs. CA 90670 Toll Free: (866) 933-7736 | Tel.: (562) 529-2938 | Fax: (562) 529-2978 Email: info@espentech.com | www.espentech.com



Wiring Diagram:



DLC Listing:

Ordering Code	DLC Product ID	DLC Product Model	DLC Version
L48T5HE/830/13G-EB-AC	N/A	N/A	N/A
L48T5HE/835/13G-EB-AC	N/A	N/A	N/A
L48T5HE/840/13G-EB-AC	N/A	N/A	N/A
L48T5HE/850/13G-EB-AC	PLBQK4GCSK84	L48T5HE/850/13G-EB-AC	5

- Please refer to "Ballast Compatibility List" for compatible battery backup and/or emergency ballasts.
- Please refer to "Ballast Compatibility List" on Related Downloads.

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

