THE POWER TO CREATE BETTER LIGHT ™

VersaKit Channel Retrofit Kit

VEKL8F/90-8XX

Commercial Grade LED Retrofit Kit



Descriptions:

This advanced channel retrofit kit easily converts 4ft Channel fluorescent wide strips to the most current LED technology. Its ultra high efficiency reduces energy costs. It is one of the LED channel retrofits that comes completely assembled as a lensed kit, requiring only one minute to install, reducing labor costs. The retrofit kit is also 0-10V Dimmable with 5 Year Warranty. Ideal applications include: office, retail, healthcare, education and hospitality interiors.

Features & Benefits:

- Performance
  The VEK series uses the latest LED technology and LED driver to ensure steady performance and long lifetime.
- Installation
  The Channel Retrofit Kit provides the ideal way to replace existing 4ft or 8ft Channel fixture, utilizing the existing fixture housing. The kit provides all the components needed to perform the change out quickly and efficiently, allowing for system upgrades without disturbing the ceiling. The LED channel retrofit is designed for width of 4.25" to 5.25" and a minimum depth of 1.625" T8/T12 fluorescent wide strips.

Specifications:

Ordering Code	Type	System Wattage	System Lumens	CCT (K)	System Efficacy	CRI	Input Voltage	Dimming	THD
VEKL8F/90-835	8ft Channel	90	11700	3500K	130	80	120-277V	0-10V	<20%
VEKL8F/90-840	8ft Channel	90	11700	4000K	130	80	120-277V	0-10V	<20%
VEKL8F/90-850	8ft Channel	90	11700	5000K	130	80	120-277V	0-10V	<20%

Wiring Diagram:

Copyright © 2008-2024. All Rights Reserved
12257 Florence Ave. | Santa Fe Springs. CA 90670
Toll Free: (866) 933-7736 | Tel.: (562) 529-2938 | Fax: (562) 529-2978
Email: info@espentech.com | www.espentech.com

THE POWER TO CREATE BETTER LIGHT ™

DLC Listing:

Ordering Code	DLC Product ID	DLC Product Model	DLC Version
VEKL8F/90-835	PLXBX7FJO05N	VEKL8F/90-835	5
VEKL8F/90-840	PLZRT43PKIP5	VEKL8F/90-840	5
VEKL8F/90-850	PL08XJ1NHJ8J	VEKL8F/90-850	5

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

Copyright © 2008-2024. All Rights Reserved
12257 Florence Ave. | Santa Fe Springs. CA 90670
Toll Free: (866) 933-7736 | Tel.: (562) 529-2938 | Fax: (562) 529-2978
Email: info@espentech.com | www.espentech.com