



Commercial Recessed Downlight
BAA/TAA Compliant

Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rated
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Works in cold temperature applications
- Flicker-free, Meets IEEE 1798-2015
- 5 Year Warranty



Specification Data

Model No.	Size	IC Rated	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Dimension
VEKR9.5D/8T/27W-10V TAA	9 in Recess	Yes	17 / 21 / 27	2070 / 2500 / 3240	3000K, 3500K, 4000K selectable	120	120-277	>80	0.9	Dia. 11.22 in x Height 5.04 in

Ordering Information

Sample model: VEKR4D/8T/10W-10V BAA

VEKR	4D	8T	10W	10V	BAA
Series Retrofit Kit Recessed Light	Size 4" Downlight	CRI>80 T: three CCT adjustable	Wattage 10W Max.	Dimming 0-10V	COO BAA TAA



User Manual

[9.5inDownlightInstallation.pdf](#)